MATERIAL SAFETY DATA SHEET

PRODUCT NAME: IXL ISSUE DATE: JANUARY 1, 2009

DIVISION AND LOCATION	SECTION 1

Division: Ambassador IXL Manufacturing Inc.
Location: 1930 West 3350 South Roy, UT 84067
Emergency Telephone Number: 800-872-4951

HAZARDOUS INGREDIENTS	SECTION 2

Chemical Name(s): N/A
Listed Carcinogen(s): None
DOT Hazard Class: N/A

HANDLING & STORAGE	SECTION 3

Do not wear contaminated clothing – wash prior to eating, drinking or use of restroom and when leaving work. Do not store near open flame or heat source. Empty containers retain product residue and may be dangerous. Do not weld, cut, braze, grind or expose to heat or flame.

PHYSICAL DATA	SECTION 4

Chemical Family: Non-hazardous/non-toxic chemical blend
Boiling Point: Unknown
Vapor Pressure: Unknown
Vapor Density (Air=1): Unknown
Solubility in Water: Nil
Specific Gravity: 1.05 – 1.3 @ 25C
Percent Volatile By Volume (%): Unknown
Evaporation Rate (BA=1): Unknown
Percent Solid By Weight (%): N/A

FIRE AND EXPLOSION HAZARD DATA	SECTION 5

Flash Point: >450 F., Method Used: C.O.C.
Flammable Limits: Not Established
Extinguishing Media: Foam, dry chemical, water spray
Special Fire Fighting Procedures: Use water spray to cool adjacent area and containers. Fire fighters should wear self-contained breathing apparatus.
Unusual Fire and Explosion Hazards: Heating of non-vented container may cause explosion. Keep surrounding containers cool with water spray.

HEALTH HAZARD DATA	SECTION 6

Symptoms of Exposure (Conditions Aggravated by Exposure): Irritation of skin may occur-a skin condition may be aggravated by exposure.
Threshold Limit Value & Permissible Exposure: Not established
Primary Routes of Entry: Skin contact
Health Hazards (Acute and Chronic): Eye irritant, frequent or prolonged contact may irritate skin. Low order of toxicity. Acute Oral LD50: 4 g/kg, mild to moderate skin irritation. Subchronic toxicity rats: NOEL-10mg/kg/day in 90 day test.
Emergency and First Aid Procedures: Eye: Immediately flush with large amounts of water. Skin: Flush with large amounts of water, use soap if available. Inhalation: Remove to fresh air. Consult physician in all cases.

REACTIVITY DATA	SECTION 7

Stability: Stable
Conditions to Avoid: Do not heat to vaporization-a possible release of hydrogen chloride, carbon monoxide may occur.
Incompatibility (Materials to Avoid): Strong oxidizing agents
Hazardous Polymerization: Will not occur

SPILL OR LEAK PROCEDURES	SECTION 8

Steps to be taken in Case Material is Released or Spilled: Wear protective clothing, dike area, prevent from entering waterway, pump from dike area to reclaim container, absorb remaining material and shovel into disposable container.
Waste Disposal Method: According to all Local, State and Federal Regulations.

SPECIAL PROTECTION INFORMATION	SECTION 9

Respiratory Protection: Not required under normal conditions and use.
Ventilation (Mechanical): Maintain concentrations below exposure limits.
Protective Gloves: Impervious
Eye Protection: Goggles and face shield.
Other Protective Equipment: Long sleeve shirt and trousers, eye wash, safety shower.

HMIS RATINGS: Health: 1, Flammability: 1, Physical hazard: 0, Personal protection: B
NFPA RATINGS: Health: 1, Flammability: 1, Instability: 0

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEROF. FOR INDUSTRIAL USE ONLY. NOT TO BE TAKEN INTERNALLY. N/A=NON APPLICABLE

AMBASSADOR IXL MANUFACTURING INC.
1930 West 3350 South
ROY, UT 84067
800-872-4951